

020-批量删除issue

```
import com.atlassian.jira.component.ComponentAccessor;
import com.atlassian.jira.issue.Issue;
import com.atlassian.jira.issue.IssueManager;
import com.atlassian.jira.user.ApplicationUser;
import com.atlassian.jira.bc.issue.search.SearchService;
import com.atlassian.jira.issue.search.SearchResults;
import com.atlassian.jira.security.JiraAuthenticationContext;
import com.atlassian.jira.web.bean.PagerFilter;

String jql = "filter = 111 ";

try {
    IssueManager issueManager = ComponentAccessor.getIssueManager();
    ApplicationUser loginUser = ComponentAccessor.getComponent(
(JiraAuthenticationContext.class).getLoggedInUser());
    SearchService searchService = ComponentAccessor.getComponentOfType(
(SearchService.class));
    SearchService.ParseResult parseResult = searchService.parseQuery(
(loginUser, jql);

    if (parseResult.isValid()) {
        SearchResults searchResults = searchService.search(loginUser,
parseResult.getQuery(), PagerFilter.getUnlimitedFilter());
        List<Issue> issueList = searchResults.getResults();
        for (int i = 0; i < issueList.size(); i++) {
            issueManager.deleteIssueNoEvent(issueList.get(i));
            //issueManager.deleteIssueNoEvent
(issueManager.getIssueObject(issueList.get(i).getId())); 不好使再用下面方法
        }
    }
} catch (Exception e) {
    e.printStackTrace();
}
```