

02- 非管理员不显示Structure菜单

Name

非管理员隐藏structure插件

An optional name, used only for your reference.

Hide what

com.almworks.jira.structure:wi-structure-link x

Select one or more module keys for web items or panels you wish to hide. Not sure where to place it? [Enable the fragment locator](#).

Condition

[Inline](#) [File](#)

[Example scripts](#)

[Fullscreen](#)

[Help](#)

[Expand editor](#)

```
1 import com.atlassian.jira.component.ComponentAccessor
2 import com.atlassian.jira.security.JiraAuthenticationContext
3 import com.atlassian.jira.user.ApplicationUser
4
5 //获取登录人
6 JiraAuthenticationContext jiraAuthenticationContext = ComponentAccessor.getCom
7 ApplicationUser currentUser = jiraAuthenticationContext.getLoggedInUser()
8 //获取所有管理员
9 Collection<ApplicationUser> applicationUsers = ComponentAccessor.getUserUtil(
10 boolean check = false
11 for(ApplicationUser admin:applicationUsers){
12     if (admin.getUsername().equals(currentUser.getUsername())) {
13         check = true
14         break
15     }
16 }
17 return check
```

17 lines

✓ No type checking errors detected

```
import com.atlassian.jira.component.ComponentAccessor
import com.atlassian.jira.security.JiraAuthenticationContext
import com.atlassian.jira.user.ApplicationUser

//获取登录人
JiraAuthenticationContext jiraAuthenticationContext = ComponentAccessor.getComponent
(JiraAuthenticationContext.class)
ApplicationUser currentUser = jiraAuthenticationContext.getLoggedInUser()
//获取所有管理员
Collection<ApplicationUser> applicationUsers = ComponentAccessor.getUserUtil().
getJiraSystemAdministrators()
boolean check = false
for(ApplicationUser admin:applicationUsers) {
    if (admin.getUsername().equals(currentUser.getUsername())) {
        check = true
        break
    }
}
return check
```