

10-向父任务写入备注

```
import com.atlassian.jira.component.ComponentAccessor;
import com.atlassian.jira.issue.CustomFieldManager;
import com.atlassian.jira.issue.Issue;
import com.atlassian.jira.issue.comments.CommentManager;
import com.atlassian.jira.issue.fields.CustomField;
import com.atlassian.jira.user.ApplicationUser;
import com.atlassian.jira.security.JiraAuthenticationContext;
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

import com.atlassian.jira.issue.customfields.option.Option;
import java.util.List;

    Issue parentIssue = issue.getParentObject();
    ApplicationUser applicationUser = ComponentAccessor.getComponent
(JiraAuthenticationContext.class).getLoggedInUser();

    CustomFieldManager customFieldManager = ComponentAccessor.
getCustomFieldManager();

    CustomField aaCf = customFieldManager.getCustomFieldObject(11701L); //评审结
果反馈
    CustomField bbCf = customFieldManager.getCustomFieldObject(11500L); //评审意
见
    CustomField ccCf = customFieldManager.getCustomFieldObject(11421L);

    StringBuffer sb = new StringBuffer();
    sb.append("#### "+applicationUser.getUsername()+" (" +applicationUser.
getDisplayname()+") ## 评审意见如下: \n");
    Option option = (Option)issue.getCustomFieldValue(aaCf);
    if(option!=null) {
        sb.append(aaCf.getName()+": "+option.getValue()).append("\n");
    }
    String value1 = (String)issue.getCustomFieldValue(bbCf);
    sb.append(bbCf.getName()+": "+value1).append("\n");

    List<Option> options = (List<Option>)issue.getCustomFieldValue(ccCf);
    if(options!=null&&options.size()>0) {
        sb.append(ccCf.getName()+":");
        for (int i = 0; i <options.size() ; i++) {
```

```
        sb.append(options.get(i).getValue()+"");  
    }  
    sb.append("\n");  
}
```

```
CommentManager commentManager = ComponentAccessor.getCommentManager();  
commentManager.create(parentIssue, applicationUser, sb.toString(), true);
```