

# 03-禁用删除issue

## 场景:

在jira权限方案中，根据项目权限方案可以控制删除，但这个使用局限性比较窄，为了更广泛的控制，可以使用scriptrunner的Fragments来控制jira删除为物理删除，而且删除后是无法找回的，在审计日志都查不到，为了收拢权限，可以将删除菜单禁用掉，指定类型，指定人员等有权删除

## 示例

[Browse](#) [Console](#) [Built-in Scripts](#) [Jobs](#) [Listeners](#) [Fields](#) [Behaviours](#) [Workflows](#) [Fragments](#) [JQL Functions](#) [REST Endpoints](#) [Resources](#) [Mail Handler](#) [Script Editor](#)

### Hide system or plugin UI element

Conditionally hides (or displays) a system web item or panel

Documentation & Tips

Name

禁用删除

An optional name, used only for your reference.

Hide what

com.atlassian.jira.plugin.system.issueoperations:delete-issue

Select one or more module keys for web items or panels you wish to hide

Condition

InlineFile

```
1 if(issue.issueType?.name == 'Story'){
2   return false;
3 }else{
4   return true;
5 }
```

Under what circumstances should this link be displayed. Must be either a plain script or an implementation of com.atlassian.plugin.web.Condition

Note that the item will be displayed if the code returns a *truthy* object.

Show snippets

Update

Preview

Cancel

## 代码

import com.atlassian.jira.component.ComponentAccessor  
import com.atlassian.jira.security.JiraAuthenticationContext  
import com.atlassian.jira.user.ApplicationUser

//获取登录人  
JiraAuthenticationContext jiraAuthenticationContext = ComponentAccessor.getComponent(JiraAuthenticationContext.class)  
ApplicationUser currentUser = jiraAuthenticationContext.getLoggedInUser()  
//判断类型并且是具体登录人可以删除  
if(issue.issueType?.name == 'Story') {  
 if(currentUser.getUsername()=='admin') {  
 return true;  
 }else{  
 return false;  
 }  
}